

## LEAF AND COIL SPRING SPECIFICATIONS

### LEAF SPRING SPECIFICATION

Spring P/N	Flat Length	Free Length	Camber	Front Eyelet	Rear Eyelet	Leaf Width	Leaves	Weight	Spring rate(lbs/in)
11211	47.00"	45.75"	3.93	1.50"	1.12"	2.50"	5	43.12lbs.	526
11411	47.00"	45.62"	4.52	1.50"	1.12"	2.50"	5	45.06lbs.	550
11511	47.62"	45.62"	6.69	1.50"	1.12"	2.50"	6	48.30lbs.	589
13211	65.66"	61.5"	9.5	0.57"	0.57"	2.50"	5	78.2lbs.	191/512
13311	53.07"	48.74"	9.17	0.57"	0.57"	2.50"	6	59.75lbs.	289/520
13411	54.56"	48.58"	10.92	0.57"	0.57"	2.50"	6	63.14lbs.	333/520
13511	57.48"	52.82"	9.84	0.57"	0.57"	2.50"	6	74.00lbs.	394/579
13611	58.54"	52.84"	10.78	0.57"	0.57"	2.50"	6	76.78lbs.	397/586
13711	66.53"	60.89"	11.45	0.57"	0.57"	2.50"	5	81.26lbs.	198/491
22210	58.80"	53.5"	6	2.00"	1.75"	3.00"	5	69.00lbs.	430
22410	58.80"	52.00"	8.1	2.00"	1.75"	3.00"	5	70.48lbs.	435
22415	62.67"	54.5"	10.7	2.00"	1.75"	3.00"	6	78.00lbs.	375
22610	59.30"	50.75"	9.75	2.00"	1.75"	3.00"	6	79.00lbs.	490
23211	56.92"	53.03"	8.89	0.57"	0.649"	3.00"	6	77.88lbs.	340/525
23311	60.1"	52.74"	12.28	0.649"	0.728"	3.00"	5	83.02lbs.	440/636
23411	58.58"	25.64"	11.14	0.57"	0.649"	3.00"	6	79.02lbs.	333/462
31211L	45.88"	42.50"	7.08	1.17"	1.17"	2.36"	3	28.14lbs.	340
31212R	45.88"	42.75"	6.57	1.17"	1.17"	2.36"	3	28.24lbs.	340
31221L	45.50"	43.25"	5.62	1.17"	1.17"	2.36"	3	28.14lbs.	301
31222R	45.50"	43.50"	5	1.17"	1.17"	2.36"	3	25.76lbs.	301
31252	44.30"	41.62"	6.4	1.37"	1.37"	2.75"	6	43.20lbs.	385
31253	44.87"	41.25"	7.91	1.38"	1.38"	2.75"	5	41.20lbs.	360
33211	51.96"	74.12"	9.44	1.25"	1.25"	60mm	4	35.86lbs.	162/340
33311	48.22"	42.44"	9.56	1.25"	1.25"	60mm	4	30.84lbs.	209/310
43211	61.02"	57.19"	9.37	0.57"	0.57"	2.50"	5	68.64lbs.	248/430
43311	60.9"	56.77"	9.4	0.649"	0.649"	3.00"	5	77.26lbs.	240/450
51212	45.00"	42.50"	6.37	1.50"	1.00"	2.00"	5	28.28lbs.	274
51213	40.62"	38.12"	6.06	0.87"	0.87"	1.77"	6	24.74lbs.	304
51222	45.62"	43.00"	6.5	1.50"	1.00"	2.50"	5	34.24lbs.	293
51223	46.75"	43.25"	6.92	0.87"	0.87"	1.77"	6	31.64lbs.	290
51313	46.00"	41.37"	8.56	1.50"	1.50"	2.50"	4	27.88lbs.	195
51323	45.87"	42.37"	7.4	1.50"	1.50"	2.50"	4	28.60lbs.	188
51412	45.12"	41.00"	8.6	1.00"	1.50"	2.00"	5	27.50lbs.	245
51413	46.00"	42.10"	7.97	1.50"	1.50"	2.50"	5	33.74lbs.	287
51422	46.19"	42.25"	8.47	1.50"	1.00"	2.50"	5	36.00lbs.	330
51423	45.87"	42.12"	7.9	1.50"	1.50"	2.50"	4	28.52lbs.	228
53111	52.12"	47.95"	8.22	0.57"	0.649"	2.50"	4	37.00lbs.	141/235

### COIL SPECIFICATIONS

P/N	Free height	Spring rate (lbs/in)	I.D. (in)	Wire Diameter	Weight (lbs)	Location
57490-1	18.87	140	4.16	0.593	10.72	Rear
55598-1	19.4	220	4.09	.625"	—	Front
55596-1	14.82	188	3.87	0.562	10.5	Front
55595-1	17.25	153	3.94	0.531	—	Rear
55594-1	16.33	148	3.9	0.531	9.5	Rear
55593-1	15.82	188	3.85	0.562	8.86	Rear
55592-1	18.3	230	4.04	0.625	14.17	Front
55498-1	15.8	175	5.38	0.625	10.72	Rear
55497-1	20.73	175	4.04	0.625"	18.22	Front
55404-1	16.1	200	5.37	0.656	13.45	Rear
55298-1	13.54	175	5.38	0.593	8.72	Rear
55297-1	17.87	170	4.04	0.593	13.22	Front
55094-3	13.98	180	3.87	.562"	10.5	Front
24615-1	21.6	740	4.02	.906-.937	29	Front
24614-1	21.5	640	3.81	.843"	30.72	Front
24613-1	21.12	430	4.06	0.812	—	Front
24612-1	20.34	450	4.04	0.782	29.22	Front
24515-1	24.57	495	4.03	.843"	NA	Front
24514-1	24.83	405	4.03	.812"	—	Front
24513-1	17.5	450	3.57	0.718	18.62	Front
24413-1	19.61	485	4.04	0.812	25.22	Front
24412-1	18.9	475	4.04	.781"	24.04	Front
24212-1	17.5	400	4.04	0.718	16.75	Front
24122-1	19.15	790	4.10	.875"	—	Front
24121-1	—	—	—	—	—	Front
15121-1	21	825	4.04	0.937	—	Front
14516-1	—	—	—	—	—	Front
14514-1	21.87	1065	—	.906"	—	Front
14122-1	18.93	285	5.10	.718"	—	Rear
14121-2	20.25	285	5.10	.718"	—	Rear
14121-1	20.25	325	5.10	0.718	—	Rear